

Polyimide Kapton® Tapes

TUFF

| Backing | Adhesive | ESD Property | Peel Strength | Liner Type | Cross Reference | Remark |
|---------------------|-------------------|--------------|---------------|-----------------------|---|--|
| 0.5mil Polyimide | Silicone | | 21 oz/in | | | Especially designed for thickness-sensitive applications |
| 1mil Dupont Kapton® | Silicone | | 25 oz/in | | 3M 5413 Nitto Permacel P-221AMB | Dupont Kapton® Film |
| 1mil Dupont Kapton® | Silicone | Anti-static | 20 oz/in | | | Dupont Kapton® Film Anti-static |
| 1mil Polyimide | Silicone | | 25 oz/in | | Nitto Permacel P-221 St. Gobain K250 CHR 2345-1 | |
| 1mil Polyimide | Silicone | Anti-static | 20 oz/in | | 3M 5419 St. Gobain K290ESD | Anti-static |
| 1mil Polyimide | Acrylic | Anti-static | 12.5 oz/in | | | Anti-static, high temp Acrylic (peak temp 500F) |
| 1mil Dupont Kapton® | Acrylic | | 25 oz/in | | 3M 7413 Nitto Permacel P-224AMB | Dupont Kapton® Film |
| 1mil Polyimide | Acrylic | | 25 oz/in | | Nitto Permacel P-224 St. Gobain K103 | |
| 1mil Polyimide | Silicone/Silicone | | 25 oz/in | Clear PET / White PET | Nitto Permacel P-223 | Double Coated Polyimide |
| 2mil Polyimide | Silicone | | 25 oz/in | | Nitto Permacel P-222 St. Gobain K350 CHR 2345-2 | |
| 2mil Polyimide | Silicone | | 25 oz/in | 2mil PET | | Linered version for efficient converting |
| 2mil Polyimide | Acrylic | | 25 oz/in | | | 2mil Polyimide with Acrylic Adhesive |
| 5mil Polyimide | Silicone | | 25 oz/in | | | 5mil Polyimide Film Backing |

**** Above is only a partial list of product SKU's available. Both product modification and new product development available upon request.***